

## M&E SERVICE MOUNTING

- 1) GAS SUPPLIES TO BE FINISHED 470mm TO THE BOTTOM OF THE VALVE 'VALVE IN DOWNWARD POSITION'. 700mm TO CENTER MANIFOLD.
- 2) DRAIN CONNECTIONS TO BE FINISHED 300mm
- 3) HOT & COLD WATER SUPPLIES TO BE FINISHE WITH SUITABLE ISOLATION VALES.
- 4) H HIGH LEVEL SOCKETS TO BE FINISHED 2200mm AFFL.
- 5) M MEDIUM LEVEL SOCKETS TO BE FINISHED 1200mm AFFL. MEDIUM LEVEL COMMANDO -SOCKETS 1450mm AFFL.
- 6) L LOW LEVEL SOCKETS TO BE FINISHED 600mm AFFL. LOW LEVEL COMMANDO SOCKETS 600mm AFFL.
- 7) DEDICATED SUPPLY TO BE FINISHED 1200mm AFFL OUTLET BOXES TO 600mm AFFL.



		SYMBOLS
REV:	DRAWING No:	<del> </del>
		GAS WATER ELECTRIC WASTE
REV:	JOB No:	COMMANDO PLUG AND SOCKET 20,30,40,50 AMPS
REV:	DATE:	ISDLATOR 20,30,40,50 AMPS
REV:	SCALE: 1:20 @ A1	ISOLATOR 3 PHASE
REV:	Drawn By:	CABLE DUTLET
	Michael Kell	FUSED SPUR DUTLET
REV:		switched socket outlet

## Signature of Approval by Client: Position Within Organisation:

PROJECT:

ALL CABLE OUTLETS 500mm F.F.L UNLESS STATED OTHERWISE.

ALL ISOLATORS AND SOCKETS 1200mm F.F.L UNLESS STATED OTHERWISE.

ALL WASTE OUTLETS TO BE 400mm F.F.L. UNLESS STATED OTHERWISE.

ALL WASTE OUTLETS TO BE 400mm F.F.L. UNLESS STATED OTHERWISE.

ALL EARTH BONDING BY ELECTRICAL CONTRACTOR TO LEE REGULATIONS.

ALL SUPPLIES MUST BE BROUGHT WITHIN ONE METRE OF EQUIPMENT BY OTHERS AND TERMINATED WITH SUITABLE GAS / WATER VALVES AND ELECTRICAL ISOLATORS.

WE RESERVE THE RIGHT TO ALTER ANY FABRICATED ITEMS TO SUIT SITE CONDITIONS.

ALL DIMENSIONS MUST BE CHECKED ON SITE AND NOT SCALED FROM THIS DRAWING.